

Komplet RV 550/F(bar.)

Komplet obsahuje: LCD 5“, venkovní kameru, konvertor, příslušenství



Voltage converter 24 volts » 12 volts

Input voltage: 20 to 30 volts DC

No-load input current: 45 mA

Nominal input current: 5 A

Nominal output current: 6 A

Peak output current: 10 A

Output voltage: 13.8 volts DC \pm 10%

Efficiency: up to 90%

Dimensions (WxHxD): 105 x 47 x 118 mm

Weight: approx. 0,45 kg

Test marks: e-approved according to 95/94/EC (EMC guidelines for vehicles)

Item designation: PerfectPower DCDC06

Ref. No.: 8006-DC24



Monitor M511L

- For 12-volt operating voltage
- TFT LCD colour monitor with 5" screen
- Real-view or mirrored picture via camera
- Two camera inputs (PAL/NTSC)
- Switches on automatically or by manual operation
- Automatic activation also with **24 volt** signals
- Loudspeaker with volume control



Camera CAM27

- CCD colour camera (PAL) with LED
- Sturdy, waterproof aluminium housing with protective steel cap and adjustable anti-dazzle sunshield
- Waterproof microphone
- Electronic brightness adjustment
- Wide-angle lens with large picture angle (120° diagonal)
- Integrated heating